

File Edit View Tools Window Help

Times New Roma 14 [Icons]

COMPENSATION TABLE

SCANTIME DURATION _____ 1

512 2 256 3 128

4 64 5 32 6 16 7 8 8 4 _____

Detailed Description Paragraph Table - DETL (16):

TABLE 17 _____ CLEAR previous
for COLUMN

= 0 to 40 step 16 'Assume we read 16-pixels/read on a '640 column LCD;

CLEAR

PACC 'Start new column with "0"; CLEAR TACC Start a new column with
"0"; forLINE = 0 to 239 'Assume a 480-line dual-scan LCD; temp = READ
(LINE,COLUMN)

'get 16-pixels from the grayscale 'full frame memory; for x = 0 to 15

'process the 16-pixels obtained with 'the 1-read; pix(x) = bit(temp,x)

'separate the 16-bits into individual 'pixels; 'the value is either 1 'or 0

(on or off 'pixel); PACC(x) = PACC(x) + pix(x) 'Running total of # pixels ON

in 'a column; trans = previous(x) (xor) pix(x) 'if the previous lines pixel
was the 'same, then transition = 0, else '1; TACC(X) = TACC(X) + trans
'Running total of # transitions in 'a column; previous(x) = pix(x) 'this
line is now "history", it will be 'used next time; next x ' next LINE ' 'at
this point, the 16-byte internal 'registers (PACC(x) and TACC(x)) 'contain
the final value for the entire 'column of 16-pixels; 'the amount of
compensation is determined next: for x = 0 to 15 comp(x) = k1 * [PACC(x) *

(1

- k2 * x/639) + k3 * TACC(x)] address = COMPADDR * 640 +
COLUMN*16 + x data= comp(x) ' WRITE (address,data) 'store it in VMEM; next x ' next
COLUMN


'Do all 40 16-pixel columns; _____

U.S. Patent

Sep. 23, 1997

Sheet 7 of 19

5,670,973



display device and its driving method

----- KWIC -----

Detailed Description Text - DETX (3):

FIG. 1 is a plan view of a liquid crystal display device of the present invention and is comprised by a liquid crystal panel 1 and driving circuits 10-12. In the liquid crystal panel a ferroelectric liquid crystal is sandwiched between an upper substrate 2 having signal electrodes 4 and a lower

substrate 3 having scanning electrodes 5. Pixel pitch is 90 .mu.m while gap between pixels is 5 .mu.m. FIG. 2 shows a section views of liquid crystal panel 1, in which each pattern of stripe-shaped transparent electrodes 4 and 5 is formed on a glass and an alignment layer 6 is formed on each electrode pattern. The liquid crystal may be an ester ferroelectric liquid crystal. The thickness of liquid crystal layer 7 is 2.0 .mu.m. Alignment layer 6 is formed by depositing SiO in a direction inclined by 82.degree. from the substrate normal line. The bright and shade pattern is displayed with a birefringence effect by pasting polarizers 9a and 9b in a right angle to each other on the upper and lower substrates. A driving circuit part is composed of a scanning electrode driving circuit (SCAN-DC) 10, a signal electrode driving circuit 11 (SIG-DC), and a base signal generating circuit 12 (BSGC). With these circuits, the driving waveform as shown in FIG. 3 is applied to each pixel of liquid crystal panel 1. The display state after the driving waveform is applied to each pixel is shown in FIG. 1 such that a dark area in liquid crystal panel is illustrated with hatching lines while a bright area is illustrated with blank white. The pixels inside 8a encircled by a solid line are applied with an ON signal while the pixels inside 8b encircled by a broken line are applied with an OFF signal. FIG. 3 (a) shows a voltage to be applied to an ON pixel connected to a certain scanning electrode, and FIG. 3 (b) a voltage to an OFF pixel connected to the following scanning electrode. Scanning by a voltage selection scheme is carried out after making the whole panel dark condition at reset phase 20. When a bipolar pulse having $V_r=25$ volt and $T_r=1$ millisecond at the part of reset phase 20 in FIG. 3 is applied over the whole panel, the liquid crystal in the panel being at a twist condition at the initial molecular orientation become a stable uniform state with a jet black including a gap area between the pixels. When the pulse of reset phase $V_r=25$ volt, T_r less than 1 millisecond and more than 500 microsecond is applied, the gap area between

United States Patent [19]

Wakita et al.

 (11) Patent Number: 5,151,803
 (45) Date of Patent: Sep. 29, 1992

[54] PIXEL-GAP CONTROLLED FERROELECTRIC LIQUID CRYSTAL DISPLAY DEVICE AND ITS DRIVING METHOD

[75] Inventors: Naohide Wakita, Osaka; Yoshio Iwai, Takasuki; Tanyoshi Uemura, Kadoma; Hiroyuki Ohnishi, Ikeda; Kamehiro Johten, Hirakata; Satoshi Kimura, Osaka; Shozo Fujiwara, Ibaraki, all of Japan

[73] Assignee: Matsushita Electric Industrial Co., Ltd., Osaka, Japan

[21] Appl. No.: 460,555

[22] Filed: Jan. 3, 1990

[30] Foreign Application Priority Data

Jan. 9, 1989 [JP] Japan 1-2412
 May 25, 1989 [JP] Japan 1-133442

[51] Int. Cl. G02F 1/133; G09G 3/26

[52] U.S. Cl. 359/85; 359/100; 340/784

[58] Field of Search 350/332, 333, 350 S, 350/341, 339 R; 340/784, 805

[56] References Cited

U.S. PATENT DOCUMENTS

4,712,872 12/1987 Kanbe et al. 350/333
 4,770,501 9/1988 Tamura et al. 359/96
 4,836,657 6/1990 Onji et al. 350/333
 4,846,560 7/1990 Tachiyama et al. 350/350 S
 4,901,066 2/1990 Kobayashi et al. 350/350 S
 4,904,057 2/1990 Sakayori et al. 350/350 S
 4,904,064 2/1990 Lagerwall et al. 350/350 S
 5,011,269 4/1991 Wakita et al. 350/350 S

FOREIGN PATENT DOCUMENTS

0179721 9/1985 Japan 350/350 S
 0269124 11/1986 Japan 350/350 S
 0295331 12/1986 Japan 350/350 S
 0102227 5/1987 Japan 350/344
 0065424 3/1988 Japan 350/350 S
 63-225234 9/1988 Japan
 63-228130 9/1988 Japan

OTHER PUBLICATIONS

"Large-Area Video-Rate Multicolor Ferroelectric Liquid-Crystal Display", S. Matsumoto et al., SID 88 Digest, 1988, pp. 41-44.
 "Structures and Applications of SSFLC Devices", N. A. Clark et al., Japan Display, 1986, pp. 456-458.
 "Black and White FLC TV Panel With Grey Levels", T. Leroux et al., 1988 International Display Research Conference, IEEE 1988, pp. 111-113.

Primary Examiner—Stanley D. Miller

Assistant Examiner—Tai Van Duong

Attorney, Agent, or Firm—Wenderoth, Lind & Ponack

[57] ABSTRACT

A liquid crystal display device and its driving method of the present invention have a voltage application scheme to control a stable condition of a gap between pixels, by applying a voltage to a liquid crystal panel in which ferroelectric liquid crystal is sandwiched between substrates each having a plurality of electrodes. It is possible to implement the black matrix conditions with a simple configuration without a light shielding layer by controlling the stable condition of the gap, to display a grey tone with a combination of pixels and a gap, or to raise the opening ratio by making the condition between adjacent pixels and a gap the same condition.

12 Claims, 10 Drawing Sheets

